

STAMPING ADHESIVE

Special for sticking plasterboard sheets on masonry walls.

ADVANTAGES

- ✓ Mix ready for use.
- ✓ Includes applicator.
- ✓ Cheaper than plastering and stucco.
- ✓ Reduced installation time.
- ✓ No waste.
- ✓ Excellent adhesion.
- ✓ Better finish.
- ✓ Easy application.
- ✓ Controlled drying that allows adjustments to plumbness.



DESCRIPTION

SUPERMASTICK PR[®] Stamping Adhesive contains vinyl polymers and other ingredients that allow excellent adhesion of gypsum boards to cement, brick or reinforced concrete walls. This adhesive produces a suction effect, immediately holding the gypsum board onto the wall. In addition, thanks to its controlled drying, it allows you to perform corrections on the plasterboards on the wall that has been covered.

BASIC APPLICATION

Make sure that the surface to be covered is completely dry and free of any dust, paint or lacquer. Trace the level. Stir the mixture before use. The application of the SUPERMASTICK PR® Stamping Adhesive can be done in strips or dots, depending on the need.

- ✓ **Application of adhesive in strips:** Fill the sleeve or applicator. Apply 5cm-wide vertical strips, starting with the edges, distributed every 30 cm over the wall to cover. It is also recommended to apply a strip of adhesive on the top and bottom of the wall to cover. Then, put the sheet on the wall pressing with a rubber hammer to evenly distribute the adhesive. Finally, level the surface with a grout-type leveler and apply joint treatment 24 hours later.
- ✓ **Application of adhesive in dots:** For easy and quick application, use the plastic sleeve. The dots should have a diameter of 10 cm, and be 5cm away from the edges of the gypsum board, distributing them every 30cm on the board in horizontal and vertical direction. The thickness of the dots will be determined by the plumbness of the wall to be covered. Level and apply joint treatment.

LIMITING FACTORS

Protect from extreme temperatures, such as prolonged exposure to sunlight or periods of freezing. Avoid using this product in places with high humidity. Surfaces must be completely clean, dry and without any kind of varnish or paint. Stir the mixture before use.

PRODUCT DATA

Material	Formulation based on polymeric adhesives and mineral fillers.
Yield	28 Kg for 7 gypsum boards approx.
Drying time	NE
Packaging	28 Kg. tub
Shelf life	6 months from the date of manufacture (under good storage conditions)

WARNING

All claims must be in writing and supported with evidence; they must be submitted in a period not greater than 30 calendar days from the date on which the defect was discovered or should have been discovered, and must be within the period of warranty. The customer should not alter or repair the affected area until Supermastick has reviewed the problem and determined a possible cause.

Avoid direct exposure to the skin. Do not inhale or ingest. Wear protective gloves and goggles.

SUPERMASTICK S.A.S. is not liable for accidental damages or their consequences, whether caused directly or indirectly, or for any loss that occurs as a result of misuse of these products, not having followed to the letter the current printed instructions or for having used them in a manner other than those specified. SUPERMASTICK S.A.S.'s liability is limited to the replacement of defective material.